
2153437-1 | CPP-SMOD-SL-1U-24



CommScope Shielded Modular Panel, SL, 1U, 24 port

Product Classification

Regional Availability	EMEA
Portfolio	CommScope®
Product Type	RJ45 patch panel
Product Series	SL Series

General Specifications

Application	For use with SL Series outlets	
Cable Type	Shielded Unshielded	
Color	Black	
Growth Configuration	Unloaded	
Interface, front	RJ45 jack	
Panel Mounting	Flush	
Panel Style	Straight	
Rack Type	EIA 19 in	
Rack Units	1	
Termination Type	IDC	
Total Ports, quantity	24	
Dimensions		
Height	44.45 mm 1.75 in	
Width	482.6 mm 19 in	
Material Specifications		
Motorial Type	Llich impact flome retordent therm	

Material Type

High-impact, flame retardant, thermoplastic | Steel

Environmental Specifications

Page 1 of 2

©2023 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: August 3, 2023



2153437-1 | CPP-SMOD-SL-1U-24

Operating Temperature -25 °C to +50 °C (-13 °F to +122 °F)

Packaging and Weights

Packaging Material	Eco-friendly, single-use plastics-free
Packaging quantity	1
Packaging Type	Bag Box

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant



Page 2 of 2

©2023 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: August 3, 2023

